



FAG

**23268-BEA-XL-K-MB1-C3**

## Spherical Roller Bearing

Spherical roller bearing 232...-BEA-XL-K-MB1, symmetric 2 outer ribs with rib washer

X-life

## Technical information



## Your current product variant

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | BEA          | With lose center lip ring         |
| Bore type                 | K            | Tapered, taper 1:12               |
| Cage                      | MB1          | Solid brass cage                  |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication facility    | Standard     |                                   |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 340 mm      | Bore diameter                     |
| D               | 620 mm      | Outside diameter                  |
| B               | 224 mm      | Width                             |
| C <sub>r</sub>  | 5.300.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 7.900.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 580.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.000 1/min | Limiting speed                    |
| n <sub>gr</sub> | 475 1/min   | Reference speed                   |
| m               | 286 kg      | Weight                            |



### Mounting dimensions

|              |        |                                       |
|--------------|--------|---------------------------------------|
| $d_{a \min}$ | 366 mm | Minimum diameter shaft shoulder       |
| $D_{a \max}$ | 594 mm | Maximum diameter of housing shoulder  |
| $r_{a \max}$ | 5 mm   | Maximum recess radius                 |
| $d_{a \max}$ | 402 mm | Maximum diameter of shaft shoulder    |
| $d_{b \min}$ | 364 mm | Minimum cavity diameter of the sleeve |
| $B_{a \min}$ | 14 mm  | Minimum cavity width of the sleeve    |

### Dimensions

|            |          |                             |
|------------|----------|-----------------------------|
| $r_{\min}$ | 6 mm     | Minimum chamfer dimension   |
| $D_1$      | 523,5 mm | Bore diameter outer ring    |
| $d_s$      | 12,5 mm  | Diameter lubrication hole   |
| $n_s$      | 23,5 mm  | Width of lubricating groove |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 200 °C | Operating temperature max. |

### Calculation factors

|       |      |                                                                                      |
|-------|------|--------------------------------------------------------------------------------------|
| $e$   | 0,36 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 1,85 | Dynamic axial load factor                                                            |
| $Y_2$ | 2,76 | Dynamic axial load factor                                                            |
| $Y_0$ | 1,81 | Static axial load factor                                                             |

### Additional information

|           |                   |
|-----------|-------------------|
| H3268-HG  | Adapter sleeve    |
| AH3268G-H | Withdrawal sleeve |



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment