


**FAG****23952-K-MB-C3**

Spherical Roller Bearing

Spherical roller bearing 239..-K-MB,
symmetric 3 ribs

Technical information



Your current product variant

Bore type	K	Tapered, taper 1:12
Cage	MB	Solid brass cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication facility	Standard	

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	360 mm	Outside diameter
B	75 mm	Width
C_r	940.000 N	Basic dynamic load rating, radial
C_{0r}	1.940.000 N	Basic static load rating, radial
C_{ur}	111.000 N	Fatigue load limit, radial
n_G	2.100 1/min	Limiting speed
n_{gr}	1.190 1/min	Reference speed
$\approx m$	22,66 kg	Weight

Mounting dimensions

$d_{a \min}$	270,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	349,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius
$d_{a \max}$	285 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	270 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	11 mm	Minimum cavity width of the sleeve



Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
D_1	330,5 mm	Bore diameter outer ring
d_s	8 mm	Diameter lubrication hole
n_s	15 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,19	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	3,54	Dynamic axial load factor
Y_2	5,27	Dynamic axial load factor
Y_0	3,46	Static axial load factor

Additional information

H3952	Adapter sleeve
AH3952G	Withdrawal sleeve



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment