

**FAG****23968-K-MB-C3**

## Spherical Roller Bearing

Spherical roller bearing 239..-K-MB,  
symmetric 3 ribs

## Technical information



## Your current product variant

Bore type	K	Tapered, taper 1:12
Cage	MB	Solid brass cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication facility	Standard	

## Main Dimensions &amp; Performance Data

d	340 mm	Bore diameter
D	460 mm	Outside diameter
B	90 mm	Width
C <sub>r</sub>	1.370.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	3.000.000 N	Basic static load rating, radial
C <sub>ur</sub>	204.000 N	Fatigue load limit, radial
n <sub>G</sub>	1.610 1/min	Limiting speed
n <sub>gr</sub>	860 1/min	Reference speed
m	41,665 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	352,4 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	447,6 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	2,5 mm	Maximum recess radius



## Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$D_1$	426,7 mm	Bore diameter outer ring
$d_s$	9,5 mm	Diameter lubrication hole
$n_s$	17,7 mm	Width of lubricating groove

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

## Calculation factors

$e$	0,18	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	3,85	Dynamic axial load factor
$Y_2$	5,73	Dynamic axial load factor
$Y_0$	3,76	Static axial load factor

## Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing
	Static angular error and misalignment
	Dynamic angular error and misalignment