


**FAG****20318-K-MB-C3** [🔗](#)

Barrel roller bearing

Barrel roller bearing 203..-K-MB

Technical information

**Your current product variant**

Bore type	K	Tapered, taper 1:12
Cage	MB	Solid brass cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN

Main Dimensions & Performance Data

d	90 mm	Bore diameter
D	190 mm	Outside diameter
B	43 mm	Width
C_r	300.000 N	Basic dynamic load rating, radial
C_{0r}	360.000 N	Basic static load rating, radial
C_{ur}	31.500 N	Fatigue load limit, radial
n_G	3.500 1/min	Limiting speed
$\approx m$	6,03 kg	Weight

Mounting dimensions

$d_{a \min}$	104 mm	Minimum diameter shaft shoulder
$D_{a \max}$	176 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius
$d_{a \max}$	113 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	96 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	6 mm	Minimum cavity width of the sleeve



Dimensions

r_{min}	3 mm	Minimum chamfer dimension
D_1	165,1 mm	Bore diameter outer ring









Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Additional information

H318	Adapter sleeve
------	----------------

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment