

**FAG****7602045-TVP** [↗](#)

Axial angular contact ball bearing

Axial angular contact ball bearing 7602...-TVP,  
single direction, no screw mounting

## Technical information

**Your current product variant**

Cage	TVP	Plastic cage
Sealing	Without	
Arrangement bearing set	Standard	Single bearing
Lubricant	Without	Not greased

**Main Dimensions & Performance Data**

d	45 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,006 mm	Bore diameter lower tolerance
D	85 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,008 mm	Outside diameter lower tolerance
B	19 mm	Width
	0 mm	Width upper tolerance
	-0,12 mm	Width lower tolerance
$C_a$	39.500 N	Basic dynamic load rating, axial
$C_{0a}$	111.000 N	Basic static load rating, axial
$C_{ua}$	5.100 N	Fatigue load limit, axial
$n_G$ Grease	4.700 1/min	Limiting speed for grease lubrication
$n_g$	2.600 1/min	Thermally safe operating speed
$\approx m$	0,498 kg	Weight



### Mounting dimensions

$D_a$	73 mm	Diameter of housing
$D_a$	H12	Diameter of housing clearance
$d_a$	57 mm	Diameter shaft
$d_a$	h12	Diameter shaft clearance

### Dimensions

$r_{min}$	1,1 mm	Minimum chamfer dimension
$r_{1 min}$	1,1 mm	Minimum chamfer dimension
$a$	66 mm	Distance between the apexes of the pressure cones
$\alpha$	60 °	Contact angle

### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

### Additional information

$M_R$	0,19 Nm	Bearing frictional torque
$c_{aL}$	1.247 N/μm	Rigidity axial
	2 μm	Axial runout
	ZM45	Recommended INA precision locknut for radial locking
	AM45	Recommended INA precision locknut for axial locking
$M_A$	65 Nm	Tightening torque for the recommended INA precision locknut
	14.410 N	Required locknut force axial



### Characteristics

---



Radial load



Axial load in one direction



Grease Lubrication



Not sealed