

**81104-TV** [↗](#)

## Axial cylindrical roller bearing

Axial cylindrical roller bearings 811, single direction, comprising K811, GS, WS



## Technical information



## Your current product variant

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

## Main Dimensions &amp; Performance Data

d	20 mm	Bore diameter
T	10 mm	Height
C <sub>a</sub>	24.900 N	Basic dynamic load rating, axial
C <sub>0a</sub>	53.000 N	Basic static load rating, axial
C <sub>ua</sub>	7.500 N	Fatigue load limit, axial
n <sub>G</sub>	10.800 1/min	Limiting speed
n <sub>gr</sub>	4.300 1/min	Reference speed
D	35 mm	Outside diameter
m	34,2 g	Weight

## Mounting dimensions

d <sub>a min</sub>	34 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	21 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	0,3 mm	Maximum recess radius



### Dimensions

D <sub>1</sub>	21 mm	Bore diameter housing washer
d <sub>1</sub>	35 mm	Rip diameter shaft washer
r <sub>min</sub>	0,3 mm	Minimum chamfer dimension

### Temperature range

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.

### Additional information

K81104-TV	Axial roller and cage assembly
GS81104	Housing Washer
WS81104	Shaft washer
LS2035	Track Washer

### Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed