

**81118-TV**

## Axial cylindrical roller bearing

Axial cylindrical roller bearings 811, single direction, comprising K811, GS, WS



## Technical information



## Your current product variant

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

## Main Dimensions &amp; Performance Data

d	90 mm	Bore diameter
T	22 mm	Height
C <sub>a</sub>	141.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	465.000 N	Basic static load rating, axial
C <sub>ua</sub>	41.000 N	Fatigue load limit, axial
n <sub>G</sub>	2.750 1/min	Limiting speed
n <sub>gr</sub>	1.070 1/min	Reference speed
D	120 mm	Outside diameter
m	0,611 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	117 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	93 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1 mm	Maximum recess radius



### Dimensions

D <sub>1</sub>	92 mm	Bore diameter housing washer
d <sub>1</sub>	120 mm	Rip diameter shaft washer
r <sub>min</sub>	1 mm	Minimum chamfer dimension




### Temperature range

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.

### Additional information

K81118-TV	Axial roller and cage assembly
GS81118	Housing Washer
WS81118	Shaft washer
LS90120	Track Washer

### Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed