

**81248-M**

Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row



Technical information



Your current product variant

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	240 mm	Bore diameter
T	78 mm	Height
C _a	1.380.000 N	Basic dynamic load rating, axial
C _{0a}	5.000.000 N	Basic static load rating, axial
C _{ua}	455.000 N	Fatigue load limit, axial
n _G	990 1/min	Limiting speed
n _{gr}	340 1/min	Reference speed
D	340 mm	Outside diameter
m	21,95 kg	Weight

Mounting dimensions

d _{a min}	335 mm	Minimum diameter shaft shoulder
D _{a max}	261 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum recess radius



Dimensions

D ₁	244 mm	Bore diameter housing washer
d ₁	335 mm	Rip diameter shaft washer
r _{min}	2,1 mm	Minimum chamfer dimension






Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K81248-M	Axial roller and cage assembly
GS81248	Housing Washer
WS81248	Shaft washer

Characteristics

	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing