

**81276-M**

## Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row

## Technical information



## Your current product variant

Cage	M	Brass Cage
------	---	------------

## Main Dimensions &amp; Performance Data

d	380 mm	Bore diameter
T	112 mm	Height
C <sub>a</sub>	2.800.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	11.100.000 N	Basic static load rating, axial
C <sub>ua</sub>	910.000 N	Fatigue load limit, axial
n <sub>G</sub>	640 1/min	Limiting speed
n <sub>gr</sub>	193 1/min	Reference speed
D	520 mm	Outside diameter
m	78,1 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	511 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	413 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	4 mm	Maximum recess radius



### Dimensions

D <sub>1</sub>	385 mm	Bore diameter housing washer
d <sub>1</sub>	515 mm	Rip diameter shaft washer
r <sub>min</sub>	4 mm	Minimum chamfer dimension


### Temperature range

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.

### Additional information

K81276-M	Axial roller and cage assembly
GS81276	Housing Washer
WS81276	Shaft washer

### Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed