
**89306-TV**

## Axial cylindrical roller bearing

Axial cylindrical roller bearings 893, single direction, comprising K893, GS, WS

## Technical information



## Your current product variant

Cage	TV	Plastic Cage made from PA66
------	----	-----------------------------

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	60 mm	Outside diameter
T	18 mm	Height
C <sub>a</sub>	69.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	197.000 N	Basic static load rating, axial
C <sub>ua</sub>	19.200 N	Fatigue load limit, axial
n <sub>G</sub>	6.400 1/min	Limiting speed
n <sub>gr</sub>	2.600 1/min	Reference speed
≈m	232,2 g	Weight

## Mounting dimensions

d <sub>a</sub>	59 mm	Minimum diameter shaft shoulder
D <sub>a</sub>	33 mm	Maximum diameter of housing shoulder
r <sub>a</sub>	1 mm	Recess radius



### Dimensions

D <sub>1</sub>	32 mm	Bore diameter housing washer
d <sub>1</sub>	60 mm	Rip diameter shaft washer
B	18 mm	Width
r <sub>min</sub>	1 mm	Minimum chamfer dimension
D <sub>c1</sub>	60 mm	Cage bore diameter



### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.

### Additional information

K89306-TV	Axial roller and cage assembly
GS89306	Housing Washer
WS89306	Shaft washer

### Characteristics

-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed