

**81244-M**

Axial cylindrical roller bearing

Axial cylindrical roller bearing 812...-M, single row



Technical information



Your current product variant

Cage	M	Brass Cage
------	---	------------

Main Dimensions & Performance Data

d	220 mm	Bore diameter
T	63 mm	Height
C _a	950.000 N	Basic dynamic load rating, axial
C _{0a}	3.450.000 N	Basic static load rating, axial
C _{ua}	320.000 N	Fatigue load limit, axial
n _G	1.110 1/min	Limiting speed
n _{gr}	410 1/min	Reference speed
D	300 mm	Outside diameter
m	13,854 kg	Weight

Mounting dimensions

d _{a min}	296 mm	Minimum diameter shaft shoulder
D _{a max}	230 mm	Maximum diameter of housing shoulder
r _{a max}	2 mm	Maximum recess radius



Dimensions

D ₁	224 mm	Bore diameter housing washer
d ₁	297 mm	Rip diameter shaft washer
r _{min}	2 mm	Minimum chamfer dimension





Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

K81244-M	Axial roller and cage assembly
GS81244	Housing Washer
WS81244	Shaft washer

Characteristics

	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed