



FAG



29488-E1-XL-MB

Axial spherical roller bearing

Axial spherical roller bearing 294..-E1-XL-MB,
with flanging ring

X-life

Technical information



Your current product variant

Heat treatment	Standard	Standard
Cage	MB	Solid brass cage
Locating feature, housing washer	Without	
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	440 mm	Bore diameter
D	780 mm	Outside diameter
T	206 mm	Section height
C_a	9.700.000 N	Basic dynamic load rating, axial
C_{0a}	32.500.000 N	Basic static load rating, axial
C_{ua}	2.900.000 N	Fatigue load limit, axial
n_G	780 1/min	Limiting speed
n_{gr}	375 1/min	Reference speed
$\approx m$	408 kg	Weight



Mounting dimensions

$d_{a \min}$	610 mm	Minimum diameter shaft shoulder
$D_{a \max}$	684 mm	Maximum diameter of housing shoulder
$D_{b \min}$	794 mm	Minimum bore diameter housing
$d_{b \max}$	477 mm	Maximum distance sleeve
$r_{a \max}$	8 mm	Maximum recess radius

Dimensions









D_1	577 mm	Bore diameter housing washer
d_1	715 mm	Rip diameter shaft washer
r_{\min}	9,5 mm	Minimum chamfer dimension
T_1	101 mm	Height of the housing washer
T_2	77 mm	Height of shaft washer
T_3	134 mm	Height of the shaft washer
T_4	199 mm	Height of shaft washer, inc. lip ring
A	257 mm	Distance of the center point

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.



Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment