
**NA2205-2RSR** [↗](#)**Yoke type track roller**

Yoke type track rollers NA22...-2RSR, single row needle roller bearings with particularly thick-walled outer ring, needle roller and cage assembly and an inner ring, without axial guidance of the outer ring, lip seal radial sealing action on both sides, inner ring can be mounted separately

Technical information**Your current product variant**

Sealing	2RSR	Lip seal on both sides
Outer ring profile	R500	R500
Relubrication facility	IR	Via inner ring lubrication hole

Main Dimensions & Performance Data

D	52 mm	Outside diameter
F	30 mm	Raceway diameter inner ring
C	17,8 mm	Width, outer ring
C _{r w}	14.500 N	Basic dynamic load rating, radial
C _{0r w}	20.300 N	Basic static load rating, radial
C _{ur w}	2.950 N	Fatigue load limit, radial
n _{D G}	1.800 1/min	Speed on permanent grease lubrication
≈m	0,209 kg	Weight

Dimensions

d	25 mm	Bore diameter
B	18 mm	Width of the bearing
D _{1 min}	38 mm	Minimum mounting dimension
r _{min}	1 mm	Minimum chamfer dimension
r _{1 min}	0,3 mm	Minimum chamfer dimension
R	500 mm	Radius of outer ring outside profile



Characteristics

-  F_r Radial load
-  L_h Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides