**NUKRE62** **Stud type track roller**

Stud type track rollers NUKRE...-A, double row cylindrical roller bearings with particularly thick-walled outer ring, full complement cylindrical roller set and with a solid roller stud with fixing thread and a mounting aid, the outer ring is guided axially by the rolling elements, labyrinth seals on both sides, with eccentric collar

Technical information**Your current product variant**

| | | |
|------------------------|-----|---|
| Sealing | 2LB | Labyrinth seals on both sides |
| Outer ring profile | IOP | Optimized INA-profile |
| Grease nipples | 2x | Drive-fit lubrication nipple unmounted 2x |
| Relubrication facility | KS | Via head and stud |
| Assembling aid head | I6 | Hexagon socket |
| Assembling aid stud | I6 | Hexagon socket |

Main Dimensions & Performance Data

| | | |
|---------------------|-------------|---|
| D | 62 mm | Outside diameter |
| d ₁ | 24 mm | Fit diameter of roller stud / stud |
| B | 80 mm | Width |
| C _{r w} | 41.000 N | Basic dynamic load rating, radial |
| C _{0r w} | 54.000 N | Basic static load rating, radial |
| C _{ur w} | 7.400 N | Fatigue load limit, radial |
| n _{D G} | 2.600 1/min | Speed on permanent grease lubrication |
| F _{0r per} | 46.000 N | Permissible static load, radial |
| F _{r per} | 23.300 N | Permissible dynamic load outer ring, radial |
| ≈m | 0,782 kg | Weight |









Dimensions

| | | |
|------------------|---------|--|
| B ₁ | 30,6 mm | Maximum width of thrust washer |
| B ₂ | 49,5 mm | Bolt/stud length effectively |
| C | 28 mm | Width, outer ring |
| C ₁ | 1,3 mm | Protrusion outer ring to thrust washer |
| r _{min} | 1 mm | Minimum chamfer dimension |
| d ₂ | 38 mm | Stop diameter of thrust washer |
| G | M24X1,5 | Thread |
| l _G | 25 mm | Thread length |
| W | 14 mm | Width of flats |
| d _e | 28 mm | Diameter of eccentric |
| B _e | 22 mm | Width, eccentric |
| e | 1 mm | Eccentricity |

Additional information

| | | |
|----------------|-----------|------------------------------|
| | NIPA3X9,5 | Drive-fit lubrication nipple |
| M _A | 220 Nm | Tightening torque nut |

Characteristics

| | |
|---|------------------------------|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Grease Lubrication |
|  | Oil Lubrication |
|  | Not sealed |