
**LR605-2RSR** **Yoke type track roller**

Yoke type track rollers LR6...-2RS/2RSR, single row self-retaining ball bearings with particularly thick-walled outer ring, ball and cage assembly and an inner ring, axial guidance of outer ring is provided by the balls, lip seal on both sides, with axial sealing action/with radial sealing action

Technical information**Your current product variant**

Sealing	2RSR	Lip seal on both sides, with radial sealing action
Outer ring profile	R500	R500
Relubrication facility	Without	Without

Main Dimensions & Performance Data

D	16 mm	Outside diameter
d	5 mm	Bore diameter
C	5 mm	Height
C _{rw}	1,290 N	Basic dynamic load rating, radial
C _{0rw}	510 N	Basic static load rating, radial
C _{urw}	26,5 N	Fatigue load limit, radial
n _{DG}	23.000 1/min	Speed on permanent grease lubrication
≈m	5,2 g	Weight

Dimensions

d ₂	7,5 mm	Diameter of thrust washer
r _{min}	0,2 mm	Minimum chamfer dimension
R	500 mm	Radius of outer ring outside profile



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides