

**LR5004-2RS**

## Yoke type track roller

Yoke type track rollers LR50..-2RS/2RSR, double row self-retaining angular contact ball bearings with particularly thick-walled outer ring, ball and cage assembly and an inner ring, axial guidance of outer ring is provided by the balls, lip seal on both sides, with axial sealing action/with radial sealing action

## Technical information



## Your current product variant

Sealing	2RS	Lip seal on both sides, with axial sealing action
Outer ring profile	R500	R500
Relubrication facility	IR	Via inner ring lubrication hole

## Main Dimensions &amp; Performance Data

D	47 mm	Outside diameter
d	20 mm	Bore diameter
C	16 mm	Height
$C_{rw}$	11.700 N	Effective dynamic load rating, radial
$C_{0rw}$	7.900 N	Effective static load rating, radial
$C_{urw}$	415 N	Effective fatigue limit load, radial
$n_{DG}$	5.500 1/min	Speed on permanent grease lubrication
$F_{rper}$	7.900 N	Permissible dynamic load, radial
$m$	0,12 kg	Weight

## Dimensions

$d_2$	25,2 mm	Diameter of thrust washer
$r_{min}$	0,6 mm	Minimum chamfer dimension
R	500 mm	Radius of outer ring outside profile



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides