

**LR5305-2Z-TVH-XL**

Yoke type track roller

Yoke type track rollers LR53...-2Z-TVH-XL, double row self-retaining angular contact ball bearings with particularly thick-walled outer ring, ball and cage assembly and an inner ring, axial guidance of outer ring is provided by the balls, lubrication hole in inner ring on request, sealing shield on both sides, cage made from glass fibre reinforced polyamide, X-life design

X-life

Technical information

Your current product variant

Sealing	2Z	Sealing shield on both sides
Outer ring profile	R500	R500
Relubrication facility	Without	Without
Cage	TVH	Solid cage made of glass-fiber reinforced polyamid PA66

Main Dimensions & Performance Data

D	72 mm	Outside diameter
d	25 mm	Bore diameter
C	25,4 mm	Height
C _{r w}	28.000 N	Effective dynamic load rating, radial
C _{0 r w}	22.500 N	Effective static load rating, radial
C _{u r w}	1.140 N	Effective fatigue limit load, radial
n _{D G}	5.700 1/min	Speed on permanent grease lubrication
F _{r per}	22.500 N	Permissible dynamic load, radial
m	0,5 kg	Weight



View product details on medias

27.06.2026, 07:51:49 KST

SCHAEFFLER

Dimensions

d_2	37,6 mm	Diameter of thrust washer
r_{min}	1,1 mm	Minimum chamfer dimension
R	500 mm	Radius of outer ring outside profile