



IMAGE COMING SOON





### PCJT20-TV-FA125.5 [↗](#)

Flanged housing unit

Flanged housing unit PCJT...-TV

## Technical information



### Your current product variant

Material	TV	Plastic
Manufacturing instruction	FA125.5	Bearing with Corroprotect coating

### Main Dimensions & Performance Data

d	20 mm	Bore diameter
L	63,8 mm	Flange width
H	114 mm	Height flange
U	38,9 mm	Total height unit
C <sub>r</sub>	12.400 N	Basic dynamic load rating, radial
C <sub>0r</sub>	6.000 N	Basic static load rating, radial
≈m	0,27 kg	Weight

### Mounting dimensions

J	90 mm	Distance fixing bore
N	11 mm	Fixing bore
n	2	Number of screwing holes



### Dimensions

A	26,5 mm	Height housing
A <sub>1</sub>	11,4 mm	Thickness of flange
A <sub>2</sub>	15,4 mm	Distance raceway
V	63,8 mm	Shoulder diameter housing
Q	1/4"-28 UNF	Connection thread for lubrication
d <sub>3</sub>	33 mm	Outside diameter locking collar

### Additional information

1	Number of housings
CJT04-TV	Housing
GRAE20-NPP-B-FA107/125.5	Bearing designation
KASK04	Protecting cap

### Temperature range

T <sub>min</sub>	-35 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.