



IMAGE  
COMING SOON**PCJT50-TV-FA125.5**

Flanged housing unit

Flanged housing unit PCJT...-TV

## Technical information

**Your current product variant**

Material	TV	Plastic
Manufacturing instruction	FA125.5	Bearing with Corroctect coating

**Main Dimensions & Performance Data**

d	50 mm	Bore diameter
L	115 mm	Flange width
H	197 mm	Height flange
U	57,8 mm	Total height unit
$C_r$	34.000 N	Basic dynamic load rating, radial
$C_{0r}$	20.800 N	Basic static load rating, radial
$\approx m$	1,179 kg	Weight

**Mounting dimensions**

J	157 mm	Distance fixing bore
N	17 mm	Fixing bore
n	2	Number of screwing holes



### Dimensions

A	43 mm	Height housing
A <sub>1</sub>	21 mm	Thickness of flange
A <sub>2</sub>	25 mm	Distance raceway
V	115 mm	Shoulder diameter housing
Q	1/4-28 UNF	Connection thread for lubrication
d <sub>3</sub>	69 mm	Outside diameter locking collar

### Additional information

1	Number of housings
CJT10-TV	Housing
GRAE50-NPP-B-FA107/125.5	Bearing designation
KASK10	Protecting cap

### Temperature range

T <sub>min</sub>	-35 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.