

IMAGE
COMING SOON**GLCTE20-FA125**

Flanged housing unit

Flanged housing unit GLCTE...-FA125

Technical information

Your current product variant


Material	GG	Grey cast iron
Manufacturing instruction	FA125	Unit with Corrotect coating, corrosion-resistant

Main Dimensions & Performance Data

d	20 mm	Bore diameter
L	66,5 mm	Flange width
H	90,5 mm	Height flange
U	33 mm	Total height unit
C_r	13.600 N	Basic dynamic load rating, radial
C_{0r}	6.600 N	Basic static load rating, radial
$\approx m$	0,41 kg	Weight

Mounting dimensions

J	71,4 mm	Distance fixing bore
N	9 mm	Fixing bore
W	3 mm	Width across flats
n	2	Number of screwing holes





Dimensions

A ₁	17 mm	Thickness of flange
A ₂	9,5 mm	Distance raceway
B ₁	31 mm	Locking collar total width
Q	M6	Connection thread for lubrication
d ₃	33 mm	Outside diameter eccentric locking collar

Additional information

1		Number of housings
GEHGLCTE04-GG-FA125.1		Housing
GRAE20-XL-NPP-B-FA125.5		Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.