

**FAG****UCF211-35**

Flanged housing unit

Flanged housing unit UCF

## Technical information

**Your current product variant**

Material	GG	Grey cast iron
----------	----	----------------

**Main Dimensions & Performance Data**

d	55,562 mm	Bore diameter
L	163 mm	Flange width
U	58,4 mm	Total height unit
C <sub>r</sub>	46.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	29.000 N	Basic static load rating, radial
C <sub>ur</sub>	1.520 N	Fatigue load limit, radial
≈m	3,29 kg	Weight

**Mounting dimensions**

J	130 mm	Distance fixing bore
N	19 mm	Fixing bore
N <sub>1</sub>	130 mm	Distance fixing bore
n	4	Number of screwing holes



### Dimensions

A	43 mm	Height housing
A <sub>1</sub>	20 mm	Thickness of flange
A <sub>2</sub>	25 mm	Distance raceway
B	55,6 mm	Width
Q	M6	Connection thread for lubrication

### Additional information

1	Number of housings
F211	Housing
UC211-35	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.