



FAG

71980-MP

Angular contact ball bearing

Angular contact ball bearing 719...-MP, single row, solid brass cage



Technische Informationen



Ваш текущий вариант продукта

Type of Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	400 mm	Bore diameter
D	540 mm	Outside diameter
B	65 mm	Width
C _r	410.000 N	Basic dynamic load rating, radial
C _{0r}	770.000 N	Basic static load rating, radial
C _{ur}	20.900 N	Fatigue load limit, radial
n _G	1.690 1/min	Limiting speed
n _{gr}	1.040 1/min	Reference speed
≈m	39,4 kg	Gewicht





Mounting dimensions

$d_{a \min}$	414,6 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	525,4 mm	Maximum diameter of housing shoulder
$D_{b \max}$	533 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1,5 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
$r_{1 \min}$	1,5 mm	Minimum chamfer dimension
D_1	488,3 mm	Shoulder diameter on outer ring wide side face
d_1	452 mm	Shoulder diameter on inner ring wide side face
a	168,2 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Характеристики

-  Радиальная нагрузка
-  Осевая нагрузка в одном направлении
-  Смазывание пластичной смазкой
-  Смазывание маслом
-  Без уплотнений
-  Крупногабаритный подшипник