



FAG

S1BCH-408-HD [↗](#)

Plummer block housing unit

FAG split cylindrical roller bearing housing

Техническая информация



Main Dimensions & Performance Data

d	4,5 in	Shaft diameter
B	18,75 in	Length base
H	12,375 in	Housing height
≈m	110 lbs	Ağırlık



Dimensions

	S1BCH-408-FL	Complete unit float
	S1BCH-408-HD	Complete unit held
	PH-7	Housing designation
A	5,625 in	Center height
C	6,75 in	Base width
D	2,375 in	Base height
E _{min}	15,75 in	Base hole distance 1 min
E _{max}	16,688 in	Base hole distance 1 max
F	4,5 in	Base hole distance 2
S	4	# of mounting bolts
S	0,75 in	Mounting bolt diameter
	S1BC-408-FL	Cartridge float bearing
	S1BC-408-HD	Cartridge held bearing
	S1C-408	Cartridge
G	5,562 in	Length through bore
L	9,125 in	Outside diameter cartridge
	1,2 lbs	Grease capacity
	48,6 lbs	Cartridge weight
	S1B-408-FL	Bearing float
	S1B-408-HD	Bearing held
	20,8 lbs	Bearing weight
	408 Grp	Housing group
C _r	62.784 lbf	Basic dynamic load rating, radial
C _{0r}	93.994 lbf	Basic static load rating, radial
C _a	650 lbf	Basic dynamic load rating, axial
	2.140 1/min	Limiting speed
D ₀	8 in	Outside diameter bearing
C ₀	3,342 in	Width inner ring
B ₀	1,844 in	Width outer ring





Просмотреть сведения о продукте на medias

26.05.2026, 14:10:07 UTC

SCHAEFFLER

