
**NK29/20-TV-XL** [↗](#)

Needle roller bearing

Needle roller bearings NK, light series

X-life

## Teknik bilgiler



## Ваш текущий вариант продукта

Lubricant	Without	
Cage	TV	Plastic Cage made from PA66
Cage feature	Standard	
Tolerance class	PN	Normal

## Main Dimensions &amp; Performance Data

$F_w$	29 mm	Under roller diameter
D	38 mm	Outside diameter
C	20 mm	Width, outer ring
$C_r$	27.500 N	Basic dynamic load rating, radial
$C_{0r}$	39.000 N	Basic static load rating, radial
$C_{ur}$	7.000 N	Fatigue load limit, radial
$n_G$	15.300 1/min	Limiting speed
$n_{gr}$	8.700 1/min	Reference speed
$m$	0,049 kg	Bec

## Dimensions

$r_{min}$	0,3 mm	Minimum chamfer dimension
-----------	--------	---------------------------



### Temperature range

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.

### Additional information

G29X38X4 Sealing ring

### Характеристики

-  Радиальная нагрузка
-  Смазывание пластичной смазкой
-  Смазывание маслом
-  Без уплотнений
-  Компактная конструкция