
**RNA4904-2RSR-RR-XL**

Radial roller bearing

Игольчатый роликоподшипник  
RNA49..-2RSR, размерная серия 49,  
контактные уплотнения с двух сторон

X-life

## Teknik bilgiler



## Mevcut ürün modeliniz

Cage	Standard	Стандарт
Radial internal clearance	CN (Group N)	Normal internal clearance
Lubrication hole	With	With
Coating	RR	покрытие Corrotect
Type of Seal	2RSR	Contact seal on both sides
Special features	Without	без
Number of rows	1	Single-row design

## Main Dimensions &amp; Performance Data

$F_w$	25 mm	Under roller diameter
D	37 mm	Outside diameter
$C_r$	19.500 N	Basic dynamic load rating, radial
$C_{0r}$	19.900 N	Basic static load rating, radial
$C_{ur}$	3.800 N	Fatigue load limit, radial
$n_G$	10.100 1/min	Limiting speed
$n_G$ Grease	10.100 1/min	Limiting speed for grease lubrication
$\approx m$	56 g	Ağırlık



### Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
C	17 mm	Width, outer ring

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Özellikleri

-  Radyal yük
-  Gres yağlama
-  Çift taraflı conta
-  Paslanmaya karşı korumalı
-  Küçük dizayn çerçevesi