
**KR72-PP-A**

Опорный ролик с цапфой

Stud type track rollers KR..-PP-A, single row needle roller bearings with particularly thick-walled outer ring, needle roller and cage assembly and a solid roller stud with fixing thread and a mounting aid, axial guidance of outer ring is provided by the plastic axial plain washers, contact flange and contact washer, three-stage sealing by plastic axial plain washer on both sides, without eccentric collar

Technical information



Ihre aktuelle Produktvariante

Уплотнение	PP	Трехступенчатое уплотнение с двух сторон с помощью пластмассовых упорных шайб
Outer ring profile	IOP	Оптимизированный профиль INA
Grease nipples	2x	Пресс-масленка, прилагается незакрепленной, 2 шт.
Relubrication facility	KSP	Через головку, цапфу и посадочное место
Assembling aid head	I6	Внутренний шестигранник
Assembling aid stud	I6	Внутренний шестигранник

Main Dimensions & Performance Data

D	72 mm	Outside diameter
d ₁	24 mm	Fit diameter of roller stud / stud
B	80 mm	Width of the roller stud
C _{r w}	28.000 N	Basic dynamic load rating, radial
C _{0r w}	53.000 N	Basic static load rating, radial
C _{ur w}	7.300 N	Fatigue load limit, radial
n _{D G}	1.900 1/min	Speed on permanent grease lubrication
≈m	0,989 kg	Gewicht







Dimensions

B ₁	30,6 mm	Maximum width of thrust washer
B ₂	49,5 mm	Bolt/stud length effectively
B ₃	11 mm	Distance to lubrication hole
C	29 mm	Width, outer ring
C ₁	0,8 mm	Protrusion outer ring to thrust washer
r _{min}	1,1 mm	Minimum chamfer dimension
d ₂	44 mm	Stop diameter of thrust washer
d ₃	4 mm	Diameter lubrication hole
G	M24X1,5	Thread
l _G	25 mm	Thread length
W	14 mm	Width of flats

Additional information

	NIPA3X9,5	Drive-fit lubrication nipple
M _A	220 Nm	Tightening torque nut

Eigenschaften

-  Radiale Last
-  Lebensdauerschmierung, Wartungsfreiheit
-  Fettschmierung
-  Beidseitig abgedichtet