


PWKR52-2RS-XL [↗](#)

Stud type track roller

Stud type track rollers PWKR..-2RS-XL, double row cylindrical roller bearings with particularly thick-walled outer ring, with a central rib, full complement cylindrical roller set and with a solid roller stud with fixing thread and a mounting aid, the outer ring is guided axially by the central rib and rolling elements, protected lip seal on both sides, without eccentric collar, X-life design

X-life

Teknik bilgiler



Mevcut ürün modeliniz

Type of Sealing	2RS	Protected lip seal on both sides
Outer ring profile	IOP	Optimized INA-profile
Grease nipples	2x	Drive-fit lubrication nipple unmounted 2x
Relubrication	KSP	Via head, stud and fit
Assembling aid head	I6	Hexagon socket
Mounting aid	I6	Hexagon socket

Main Dimensions & Performance Data

D	52 mm	Outside diameter
d ₁	20 mm	Fit diameter of roller stud / stud
B	66 mm	Width
C _{r w}	25.500 N	Basic dynamic load rating, radial
C _{0r w}	33.500 N	Basic static load rating, radial
C _{ur w}	4.200 N	Fatigue load limit, radial
n _{D G}	3.800 1/min	Speed on permanent grease lubrication
F _{0r per}	33.500 N	Permissible static load, radial
F _{r per}	21.800 N	Permissible dynamic load outer ring, radial
≈m	0,504 kg	Ağırlık









Dimensions

B ₁	25,6 mm	Width of thrust washer
B ₂	40,5 mm	Bolt/stud length effectively
B ₃	9 mm	Distance to lubrication hole
C	24 mm	Width, outer ring
C ₁	0,8 mm	Protrusion outer ring to thrust washer
r _{min}	1 mm	Minimum chamfer dimension
d ₂	31 mm	Stop diameter of thrust washer
d ₃	4 mm	Diameter lubrication hole
G	M20X1,5	Thread
I _G	21 mm	Thread length
W	10 mm	Width of flats

Additional information

	NIPA2X7,5	Drive-fit lubrication nipple
M _A	120 Nm	Tightening torque nut

Özellikleri

-  Radyal yük
-  Tek yönde aksel yük
-  İki yönde aksel yük
-  Ömür boyu yağlama, bakım gerektirmez
-  Gres yağlama
-  Çift taraflı conta